

数据科学导论实验报告

实验二 熟悉常用的 HDFS 操作



学 生：

年 级：2021 级

专 业：软件工程

重庆大学大数据与软件学院

2023 年 10 月 13 日

一、 实验目的：

1. 理解 HDFS 在 Hadoop 体系结构中的角色：通过实验，学习者将深入理解 HDFS 在 Hadoop 生态系统中的重要性和角色。HDFS 是 Hadoop 的分布式文件系统，用于存储和管理大数据，因此掌握其操作对于整个 Hadoop 平台的理解至关重要；

2. 熟练使用 HDFS 操作常用的 Shell 命令：实验的目的是帮助学习者熟练掌握 Hadoop Shell 命令，这些命令是与 HDFS 交互的关键工具。学习者将学会如何上传、下载、查看、创建、删除、移动等 HDFS 文件和目录，这些命令对于大数据处理和数据管理非常重要；

3. 熟悉 HDFS 操作常用的 Java API：实验不仅涉及 Shell 命令，还要求学习者使用 Java 编程语言来执行 HDFS 操作。通过编程实践，学习者将熟悉 Hadoop 提供的 Java API，了解如何在自己的应用程序中集成 HDFS 操作，以实现更高级的数据处理任务。这有助于学习者进一步深入学习大数据应用开发和数据分析。

二、 实验要求

1. 编程实现以下指定功能，并利用 Hadoop 提供的 Shell 命令完成相同任务：

(1) 向 HDFS 中上传任意文本文件，如果指定的文件在 HDFS 中已经存在，由用户指定是追加到原有文件末尾还是覆盖原有的文件；

(2) 从 HDFS 中下载指定文件，如果本地文件与要下载的文件名称相同，则自动对下载的文件重命名；

(3) 将 HDFS 中指定文件的内容输出到终端中；

(4) 显示 HDFS 中指定的文件的读写权限、大小、创建时间、路径等信息；

(5) 给定 HDFS 中某一个目录，输出该目录下的所有文件的读写权限、大小、创建时间、路径等信息，如果该文件是目录，则递归输出该目录下所有文件相关信息；

(6) 提供一个 HDFS 内的文件的路径，对该文件进行创建和删除操作。如果文件所在目录不存在，则自动创建目录；

(7) 提供一个 HDFS 的目录的路径，对该目录进行创建和删除操作。创建目录时，如果目录文件所在目录不存在则自动创建相应目录；删除目录时，由用户指定当该目录不为空时是否还删除该目录；

(8) 向 HDFS 中指定的文件追加内容，由用户指定内容追加到原有文件的开头或结尾；

(9) 删除 HDFS 中指定的文件；

(10) 删除 HDFS 中指定的目录，由用户指定目录中如果存在文件时是否删除目录；

(11) 在 HDFS 中，将文件从源路径移动到目的路径。

2. 编程实现一个类“`MyFSDataInputStream`”，该类继承“`org.apache.hadoop.fs.FSDataInputStream`”，要求如下：

实现按行读取 HDFS 中指定文件的方法“`readLine()`”，如果读到文件末尾，则返回空，否则返回文件一行的文本。

3. 查看 Java 帮助手册或其它资料，用 "java.net.URL" 和 "org.apache.hadoop.fs.FsURLStreamHandlerFactory" 编程完成输出 HDFS 中指定文件的文本到终端中。

三、 开发环境：

- Lenovo Legion R9000P2021H
- VMware-workstation-full-17.0.0
- Bbuntu Kylin 16.04
- Eclipse-4.7.0-linux.gtk.x86_64


四、 实验内容：

1. 编程实现以下指定功能，并利用 Hadoop 提供的 Shell 命令完成相同任务：

(1) 向 HDFS 中上传任意文本文件，如果指定的文件在 HDFS 中已经存在，由用户指定是追加到原有文件末尾还是覆盖原有的文件；

①Shell 命令：

a. 本地 test 文本内容



b. 上传 test，检测文件是否存在，显示文件内容

```
Terminal File Edit View Search Terminal Help
hadoop@ubuntu:~$ cd /usr/local/hadoop
hadoop@ubuntu:/usr/local/hadoop$ ./sbin/start-dfs.sh
Starting namenodes on [localhost]
localhost: namenode is running as process 2812. Stop it first.
Starting datanodes
localhost: datanode is running as process 2978. Stop it first.
Starting secondary namenodes [ubuntu]
ubuntu: secondarynamenode is running as process 3183. Stop it first.
hadoop@ubuntu:/usr/local/hadoop$ ./bin/hdfs dfs -put test.txt /fileTest/
2023-10-12 06:54:10,708 INFO sasl.SaslDataTransferClient: SASL encryption trust check: localhostTrusted = false, remoteHostTrusted = false
hadoop@ubuntu:/usr/local/hadoop$ ./bin/hdfs dfs -test -e /fileTest/test.txt
0
hadoop@ubuntu:/usr/local/hadoop$ echo $?
0
hadoop@ubuntu:/usr/local/hadoop$ ./bin/hdfs dfs -cat /fileTest/test.txt
Test
2023-10-12 06:55:01,848 INFO sasl.SaslDataTransferClient: SASL encryption trust check: localhostTrusted = false, remoteHostTrusted = false
Test
hadoop@ubuntu:/usr/local/hadoop$ ./bin/hdfs dfs -appendToFile test.txt /fileTest/test.txt
2023-10-12 07:00:44,537 INFO sasl.SaslDataTransferClient: SASL encryption trust check: localhostTrusted = false, remoteHostTrusted = false
hadoop@ubuntu:/usr/local/hadoop$ ^C
hadoop@ubuntu:/usr/local/hadoop$ ./bin/hdfs dfs -cat /fileTest/test.txt
Test
Test
hadoop@ubuntu:/usr/local/hadoop$
```

测试文件是否存在，0表示存在

输出文件内容，与本地文件符合

再次上传文件，将内容添加至以存在文件末尾

输出文件内容，与预期相符合

c. 使用本地文件覆盖 HDFS 文件

```
Terminal File Edit View Search Terminal Help
hadoop@ubuntu:~$ cd /usr/local/hadoop
hadoop@ubuntu:/usr/local/hadoop$ ./bin/hdfs dfs -copyFromLocal -f test.txt /fileTest/test.txt
2023-10-12 07:10:28,190 INFO sasl.SaslDataTransferClient: SASL encryption trust check: localhostTrusted = false, remoteHostTrusted = false
hadoop@ubuntu:/usr/local/hadoop$ ./bin/hdfs dfs -cat /fileTest/test.txt
Test
2023-10-12 07:11:13,629 INFO sasl.SaslDataTransferClient: SASL encryption trust check: localhostTrusted = false, remoteHostTrusted = false
Test
hadoop@ubuntu:/usr/local/hadoop$
```

使用本地文件覆盖hdfs中的test.txt

输出文件内容，覆盖成功

②Java:

源代码:

```
import java.io.FileInputStream;
import java.io.IOException;
import org.apache.hadoop.conf.Configuration;
import org.apache.hadoop.fs.FSDataOutputStream;
import org.apache.hadoop.fs.FileSystem;
import org.apache.hadoop.fs.Path;
public class CopyFromLocalFile {
    /**
     * 判断路径是否存在
     */
    public static boolean test(Configuration conf, String path) {
        try (FileSystem fs = FileSystem.get(conf)) {
            return fs.exists(new Path(path));
        } catch (IOException e) {
            e.printStackTrace();
            return false;
        }
    }

    /**
     * 复制文件到指定路径 若路径已存在, 则进行覆盖
     */
    public static void copyFromLocalFile(Configuration conf,
        String localFilePath, String remoteFilePath) {
        Path localPath = new Path(localFilePath);
        Path remotePath = new Path(remoteFilePath);
        try (FileSystem fs = FileSystem.get(conf)) {
            /* fs.copyFromLocalFile 第一个参数表示是否删除源文件, 第二个参数表示是否覆盖 */
            fs.copyFromLocalFile(false, true, localPath, remotePath);
        } catch (IOException e) {
            e.printStackTrace();
        }
    }

    /**
     * 追加文件内容
     */
    public static void appendToFile(Configuration conf, String localFilePath,
        String remoteFilePath) {
        Path remotePath = new Path(remoteFilePath);
        try (FileSystem fs = FileSystem.get(conf);
            FileInputStream in = new FileInputStream(localFilePath);) {
            FSDataOutputStream out = fs.append(remotePath);
            byte[] data = new byte[1024];
            int read = -1;
            while ((read = in.read(data)) > 0) {
                out.write(data, 0, read);
            }
            out.close();
        } catch (IOException e) {
            e.printStackTrace();
        }
    }


    /**
     * 主函数
     */
    public static void main(String[] args) {
        Configuration conf = new Configuration();
        conf.set("fs.defaultFS", "hdfs://localhost:9000");
        String localFilePath = "/usr/local/hadoop/text.txt"; // 本地路径
        String remoteFilePath = "/user/hadoop/file/text.txt"; // HDFS路径
        // String choice = "append"; // 若文件存在则追加到文件末尾
        String choice = "overwrite"; // 若文件存在则覆盖

        try {
            /* 判断文件是否存在 */
            boolean fileExists = false;
            if (CopyFromLocalFile.test(conf, remoteFilePath)) {
                fileExists = true;
                System.out.println(remoteFilePath + " 已存在.");
            } else {
                System.out.println(remoteFilePath + " 不存在.");
            }
            /* 进行处理 */
            if (!fileExists) { // 文件不存在, 则上传
                CopyFromLocalFile.copyFromLocalFile(conf, localFilePath,
                    remoteFilePath);
                System.out.println(localFilePath + " 已上传至 " + remoteFilePath);
            } else if (choice.equals("overwrite")) { // 选择覆盖
                CopyFromLocalFile.copyFromLocalFile(conf, localFilePath,
                    remoteFilePath);
                System.out.println(localFilePath + " 已覆盖 " + remoteFilePath);
            } else if (choice.equals("append")) { // 选择追加
                CopyFromLocalFile.appendToFile(conf, localFilePath,
                    remoteFilePath);
                System.out.println(localFilePath + " 已追加至 " + remoteFilePath);
            }
        } catch (Exception e) {
            e.printStackTrace();
        }
    }
}
```


实验二

实现结果：

a. 当文件在 HDFS 中不存在时




b. 当文件在 HDFS 中已经存在时




(2) 从 HDFS 中下载指定文件，如果本地文件与要下载的文件名称相同，则自动对下载的文件重命名；

①Shell 命令：


a. 操作前的文件目录



b. 文件下载，若与 test 重名，则重命名为 test2



c. 操作后的文件目录



②Java:

源代码:

```
import org.apache.hadoop.conf.Configuration;
import org.apache.hadoop.fs.*;
import org.apache.hadoop.fs.FileSystem;


import java.io.*;

public class CopyToLocal {
    /**
     * 下载文件到本地 判断本地路径是否已存在, 若已存在, 则自动进行重命名
     */
    public static void copyToLocal(Configuration conf, String remoteFilePath,
                                   String localFilePath) {
        Path remotePath = new Path(remoteFilePath);
        try (FileSystem fs = FileSystem.get(conf)) {
            File f = new File(localFilePath);
            /* 如果文件名存在, 自动重命名(在文件名后面加上 _0, _1 ...) */
            if (f.exists()) {
                System.out.println(localFilePath + " 已存在.");
                Integer i = Integer.valueOf(0);
                while (true) {
                    f = new File(localFilePath + "_" + i.toString());
                    if (!f.exists()) {
                        localFilePath = localFilePath + "_" + i.toString();
                        break;
                    } else {
                        i++;
                        continue;
                    }
                }
                System.out.println("将重新命名为: " + localFilePath);
            }
            // 下载文件到本地
            Path localPath = new Path(localFilePath);
            fs.copyToLocalFile(remotePath, localPath);
        } catch (IOException e) {
            // TODO Auto-generated catch block
            e.printStackTrace();
        }
    }

    /**
     * 主函数
     */
    public static void main(String[] args) {
        Configuration conf = new Configuration();
        conf.set("fs.defaultFS", "hdfs://localhost:9000");
        String localFilePath = "/usr/local/hadoop/text.txt"; // 本地路径
        String remoteFilePath = "/user/hadoop/file/text.txt"; // HDFS路径

        try {
            CopyToLocal.copyToLocal(conf, remoteFilePath, localFilePath);
            System.out.println("下载完成");
        } catch (Exception e) {
            e.printStackTrace();
        }
    }
}
```


实现结果：



(3) 将 HDFS 中指定文件的内容输出到终端中；

①Shell 命令：

将 test.txt 的内容输出至终端




②Java:

源代码:

```
import org.apache.hadoop.conf.Configuration;
import org.apache.hadoop.fs.*;
import java.io.*;

public class HDFSOutput {
    /**
     * 读取文件内容
     */
    public static void HDFSOutput(Configuration conf, String remoteFilePath)
        throws IOException {
        FileSystem fs = FileSystem.get(conf);
        Path remotePath = new Path(remoteFilePath);
        FSDataInputStream in = fs.open(remotePath);
        BufferedReader d = new BufferedReader(new InputStreamReader(in));
        String line = null;
        while ((line = d.readLine()) != null) {
            System.out.println(line);
        }
        d.close();
        in.close();
        fs.close();
    }
}
```


实现结果:



(4) 显示 HDFS 中指定的文件的读写权限、大小、创建时间、路径等信息；

①Shell 命令：

输出 test.txt 的相关信息



```
hadoop@ubuntu:~$ cd /usr/local/hadoop
hadoop@ubuntu:~$ ./bin/hdfs dfs -ls -h /fileTest/test.txt
-rw-r--r-- 1 hadoop supergroup 5 2023-10-12 07:10 /fileTest/test.txt
hadoop@ubuntu:~$
```

输出test.txt的相关信息

②Java：

源代码：

```
import org.apache.hadoop.conf.Configuration;
import org.apache.hadoop.fs.*;
import java.io.*;
import java.text.SimpleDateFormat;

public class HDFSReadAndShowDetail {
    public static void main(String[] args) {
        Configuration conf = new Configuration();
        conf.set("fs.defaultFS", "hdfs://localhost:9000");
        String remoteFilePath = "/user/hadoop/file1.txt";
        try {
            FileSystem fs = FileSystem.get(conf);
            Path remotePath = new Path(remoteFilePath);
            FileStatus[] fileStatuses = fs.listStatus(remotePath);
            for (FileStatus s : fileStatuses) {
                System.out.println("路径:" + s.getPath().toString());
                System.out.println("权限:" + s.getPermission().toString());
                System.out.println("大小:" + s.getLen());

                Long timeStamp = s.getModificationTime();
                SimpleDateFormat format = new SimpleDateFormat(
                    "yyyy-MM-dd HH:mm:ss");
                String date = format.format(timeStamp);
                System.out.println("时间: " + date);
            }
            fs.close();
        } catch (Exception e) {
            e.printStackTrace();
        }
    }
}
```


实现结果:

```
<terminated> HDFSReadAndShowDetail [Java Application] /usr/lib/jvm/jdk1.8.0_162/bin/java (Oct 3, 2023, 7:05:18)
log4j:WARN No appenders could be found for logger (org.apache.hadoop.util.Shell).
log4j:WARN Please initialize the log4j system properly.
log4j:WARN See http://logging.apache.org/log4j/1.2/faq.html#noconfig for more info.
路径:hdfs://localhost:9000/user/hadoop/file1.txt
权限:rw-r--r--
大小:19
时间: 2023-09-22 20:47:24
```

(5) 给定 HDFS 中某一个目录，输出该目录下的所有文件的读写权限、大小、创建时间、路径等信息，如果该文件是目录，则递归输出该目录下所有文件相关信息；

①Shell 命令：

输出 fileTest 目录下的所有文件相关信息

A terminal window titled "Terminal File Edit View Search Terminal Help" is shown. The user is at the prompt "hadoop@ubuntu:~\$". They enter the command "cd /usr/local/hadoop". The prompt changes to "hadoop@ubuntu:/usr/local/hadoop\$". They then enter the command "./bin/hdfs dfs -ls -R -h /fileTest". The output is displayed on the next line: "-rw-r--r-- 1 hadoop supergroup 5 2023-10-12 07:10 /fileTest/test.txt". The prompt returns to "hadoop@ubuntu:/usr/local/hadoop\$".

```
hadoop@ubuntu:~$ cd /usr/local/hadoop
hadoop@ubuntu:/usr/local/hadoop$ ./bin/hdfs dfs -ls -R -h /fileTest
-rw-r--r-- 1 hadoop supergroup 5 2023-10-12 07:10 /fileTest/test.txt
hadoop@ubuntu:/usr/local/hadoop$
```

输出fileTest目录下所有文件的相关信息

②Java:

源代码:

```
import org.apache.hadoop.conf.Configuration;
import org.apache.hadoop.fs.*;
import java.io.*;
import java.text.SimpleDateFormat;

public class HDFSFileInformationReader {
    public static void main(String[] args) {
        Configuration conf = new Configuration();
        conf.set("fs.defaultFS", "hdfs://localhost:9000");
        String remoteDir = "/user/hadoop";
        try {
            System.out.println("读目录: " + remoteDir);

            FileSystem fs = FileSystem.get(conf);
            Path dirPath = new Path(remoteDir);
            RemoteIterator<LocatedFileStatus> remoteIterator = fs.listFiles(dirPath, true);
            while (remoteIterator.hasNext()) {
                FileStatus s = remoteIterator.next();
                System.out.println("路径:" + s.getPath().toString());
                System.out.println("权限:" + s.getPermission().toString());
                System.out.println("大小:" + s.getLen());

                /* 返回的是时间戳转化为时间日期格式 */
                Long timeStamp = s.getModificationTime();
                SimpleDateFormat format = new SimpleDateFormat("yyyy-MM-dd HH:mm:ss");
                String date = format.format(timeStamp);
                System.out.println("时间:" + date);
                System.out.println();
            }

            fs.close();
            System.out.println("读取完成");
        } catch (Exception e) {
            e.printStackTrace();
        }
    }
}
```

实现结果:

```
<terminated> HDFSFileInformationReader [Java Application] /usr/lib/jvm/jdk1.8.0_162/bin/java (Oct 3, 2023, 7:05:46 PM)
路径:hdfs://localhost:9000/user/hadoop/file1.txt
权限:rw-r--r--
大小:19
时间:2023-09-22 20:47:24

路径:hdfs://localhost:9000/user/hadoop/file2.txt
权限:rw-r--r--
大小:19
时间:2023-09-22 20:47:24

路径:hdfs://localhost:9000/user/hadoop/file3.txt
权限:rw-r--r--
大小:19
时间:2023-09-22 20:47:24
```

(6) 提供一个 HDFS 内的文件的路径, 对该文件进行创建和删除操作。如果文件所在目录不存在, 则自动创建目录;

①Shell 命令:

a. 按路径创建文件, 若路径不存在先创建路径

```
hadoop@ubuntu:~$ cd /usr/local/hadoop
hadoop@ubuntu:~/local/hadoop$ ./bin/hdfs dfs -ls -R -h /
drwxr-xr-x - hadoop supergroup 0 2023-10-12 07:10 /fileTest
-rw-r--r-- 1 hadoop supergroup 5 2023-10-12 07:10 /fileTest/test.txt
hadoop@ubuntu:~/local/hadoop$ if $(./bin/hdfs dfs -test -d /usr/data/dataFile);
> then $(./bin/hdfs dfs -touchz /usr/local/dataFile/a.txt);
> else $(./bin/hdfs dfs -mkdir -p /usr/local/dataFile && ./bin/hdfs dfs -touchz /usr/local/dataFile/a.txt);
> fi
hadoop@ubuntu:~/local/hadoop$ ^C
hadoop@ubuntu:~/local/hadoop$ ./bin/hdfs dfs -ls -R -h /
drwxr-xr-x - hadoop supergroup 0 2023-10-12 07:10 /fileTest
-rw-r--r-- 1 hadoop supergroup 5 2023-10-12 07:10 /fileTest/test.txt
drwxr-xr-x - hadoop supergroup 0 2023-10-12 07:57 /usr
drwxr-xr-x - hadoop supergroup 0 2023-10-12 07:57 /usr/local
drwxr-xr-x - hadoop supergroup 0 2023-10-12 07:57 /usr/local/dataFile
-rw-r--r-- 1 hadoop supergroup 0 2023-10-12 07:57 /usr/local/dataFile/a.txt
```

创建文件同时检测指定路径是否存在
若不存在则先创建路径

创建结果

b. 按路径删除文件

```
hadoop@ubuntu:~$ cd /usr/local/hadoop
hadoop@ubuntu:~/local/hadoop$ ./bin/hdfs dfs -ls -R -h /
drwxr-xr-x - hadoop supergroup 0 2023-10-12 07:10 /fileTest
-rw-r--r-- 1 hadoop supergroup 5 2023-10-12 07:10 /fileTest/test.txt
drwxr-xr-x - hadoop supergroup 0 2023-10-12 07:57 /usr
drwxr-xr-x - hadoop supergroup 0 2023-10-12 07:57 /usr/local
drwxr-xr-x - hadoop supergroup 0 2023-10-12 08:07 /usr/local/dataFile
-rw-r--r-- 1 hadoop supergroup 0 2023-10-12 08:07 /usr/local/dataFile/a.txt
hadoop@ubuntu:~/local/hadoop$ if $(./bin/hdfs dfs -test -d /usr/data/dataFile);
> then $(./bin/hdfs dfs -rm -r /usr/local/dataFile/a.txt);
> else $(./bin/hdfs dfs -mkdir -p /usr/local/dataFile && ./bin/hdfs dfs -rm -r /usr/local/dataFile/a.txt);
> fi
Deleted: command not found
hadoop@ubuntu:~/local/hadoop$ ./bin/hdfs dfs -ls -R -h /
drwxr-xr-x - hadoop supergroup 0 2023-10-12 07:10 /fileTest
-rw-r--r-- 1 hadoop supergroup 5 2023-10-12 07:10 /fileTest/test.txt
drwxr-xr-x - hadoop supergroup 0 2023-10-12 07:57 /usr
drwxr-xr-x - hadoop supergroup 0 2023-10-12 07:57 /usr/local
drwxr-xr-x - hadoop supergroup 0 2023-10-12 08:08 /usr/local/dataFile
```

按路径删除文件

删除成功

②Java:

源代码:

```
import org.apache.hadoop.conf.Configuration;
import org.apache.hadoop.fs.*;
import java.io.*;

public class HDFSSetup {
    public static void main(String[] args) {
        Configuration conf = new Configuration();
        conf.set("fs.default.name", "hdfs://localhost:9000");
        String remoteFilePath = "/user/hadoop/ex4/test.txt"; // HDFS路径
        String remoteDir = "/user/hadoop/ex4"; // HDFS路径对应的目录
        try {
            FileSystem fs = FileSystem.get(conf);

            boolean fileExists = fs.exists(new Path(remoteFilePath));
            boolean dirExists = fs.exists(new Path(remoteDir));

            if (fileExists) {
                deleteFile(fs, remoteFilePath);
                System.out.println("删除路径: " + remoteFilePath);
            } else {
                if (!dirExists) {
                    createDirectory(fs, remoteDir);
                    System.out.println("创建文件夹: " + remoteDir);
                    createFile(fs, remoteFilePath);
                    System.out.println("创建路径: " + remoteFilePath);
                }
            }

            fs.close();
        } catch (Exception e) {
            e.printStackTrace();
        }
    }


    private static void deleteFile(FileSystem fs, String remoteFilePath) throws IOException {
        Path remotePath = new Path(remoteFilePath);
        fs.delete(remotePath, false);
    }

    private static void createDirectory(FileSystem fs, String remoteDir) throws IOException {
        Path dirPath = new Path(remoteDir);
        fs.mkdirs(dirPath);
    }

    private static void createFile(FileSystem fs, String remoteFilePath) throws IOException {
        Path remotePath = new Path(remoteFilePath);
        FSDataOutputStream outputStream = fs.create(remotePath);
        outputStream.close();
    }
}
```

实现结果：

a. 原本目录不存在，我们运行程序，程序提示已经创建，用 shell 命令进行验证，可以发现，文件确已创建；



```
HDFSSetup.java
import org.apache.hadoop.conf.Configuration;
import org.apache.hadoop.fs.*;
import java.io.*;

public class HDFSSetup {
    public static void main(String[] args) {
        Configuration conf = new Configuration();
        conf.set("fs.default.name", "hdfs://localhost:9000");
        String remoteFilePath = "/user/hadoop/ex4/test.txt";
        String remoteDir = "/user/hadoop/ex4"; // HDFS路径对应的
        try {
            FileSystem fs = FileSystem.get(conf);

            boolean fileExists = fs.exists(new Path(remoteFilePath));
            boolean dirExists = fs.exists(new Path(remoteDir));

            if (!dirExists) {
                fs.mkdirs(new Path(remoteDir));
            }

            if (!fileExists) {
                fs.create(new Path(remoteFilePath));
            }
        } catch (IOException e) {
            e.printStackTrace();
        }
    }
}


<terminated> HDFSSetup [Java Application] /usr/lib/jvm/jdk1.8.0_162/bin/java (O
log4j:WARN No appenders could be found for logger (org.apache.hadoop
log4j:WARN Please initialize the log4j system properly.
log4j:WARN See http://logging.apache.org/log4j/1.2/faq.html#noconfig
创建文件夹: /user/hadoop/ex4
创建路径: /user/hadoop/ex4/test.txt

Hadoop
Spark
CQU DataSenseClass

hadoop@aaronhowell-virtual-machine: /usr/local/hadoop
this is file3.txt

hadoop@aaronhowell-virtual-machine: /usr/local/hadoop$ ./bin/hdfs dfs -put /home/
hadoop/*.abc /user/hadoop/
2023-09-22 20:53:08,903 INFO sasl.SaslDataTransferClient: SASL encryption trust
check: localhostTrusted = false, remoteHostTrusted = false
2023-09-22 20:53:08,999 INFO sasl.SaslDataTransferClient: SASL encryption trust
check: localhostTrusted = false, remoteHostTrusted = false
hadoop@aaronhowell-virtual-machine: /usr/local/hadoop$ hdfs dfs -ls /user/hadoop/
ex4
Command 'hdfs' not found, did you mean:
  command 'hdfsls' from deb hdf4-tools (4.2.15-4)
  command 'hfs' from deb hfsutils-tcltk (3.2.6-15build2)
Try: sudo apt install <deb name>
hadoop@aaronhowell-virtual-machine: /usr/local/hadoop$ ./bin/hdfs dfs -ls /user/h
adoop/ex4
Found 1 items
-rw-r--r-- 3 hadoop supergroup 0 2023-10-03 19:23 /user/hadoop/ex4/te
st.txt
hadoop@aaronhowell-virtual-machine: /usr/local/hadoop$
```

b. 再次运行程序，此时程序应该删除指定文件；



```
HDFSSetup.java
import org.apache.hadoop.conf.Configuration;
import org.apache.hadoop.fs.*;
import java.io.*;

public class HDFSSetup {
    public static void main(String[] args) {
        Configuration conf = new Configuration();
        conf.set("fs.default.name", "hdfs://localhost:9000");
        String remoteFilePath = "/user/hadoop/ex4/test.txt";
        String remoteDir = "/user/hadoop/ex4"; // HDFS路径对应的
        try {
            FileSystem fs = FileSystem.get(conf);

            boolean fileExists = fs.exists(new Path(remoteFilePath));
            boolean dirExists = fs.exists(new Path(remoteDir));

            if (dirExists) {
                fs.delete(new Path(remoteDir), true);
            }

            if (fileExists) {
                fs.delete(new Path(remoteFilePath));
            }
        } catch (IOException e) {
            e.printStackTrace();
        }
    }
}

<terminated> HDFSSetup [Java Application] /usr/lib/jvm/jdk1.8.0_162/bin/java (O
log4j:WARN No appenders could be found for logger (org.apache.hadoop
log4j:WARN Please initialize the log4j system properly.
log4j:WARN See http://logging.apache.org/log4j/1.2/faq.html#noconfig
删除路径: /user/hadoop/ex4/test.txt

Hadoop
Spark
CQU DataSenseClass

hadoop@aaronhowell-virtual-machine: /usr/local/hadoop
this is file3.txt

hadoop@aaronhowell-virtual-machine: /usr/local/hadoop$ ./bin/hdfs dfs -put /home/
hadoop/*.abc /user/hadoop/
2023-09-22 20:53:08,903 INFO sasl.SaslDataTransferClient: SASL encryption trust
check: localhostTrusted = false, remoteHostTrusted = false
2023-09-22 20:53:08,999 INFO sasl.SaslDataTransferClient: SASL encryption trust
check: localhostTrusted = false, remoteHostTrusted = false
hadoop@aaronhowell-virtual-machine: /usr/local/hadoop$ hdfs dfs -ls /user/hadoop/
ex4
Command 'hdfs' not found, did you mean:
  command 'hdfsls' from deb hdf4-tools (4.2.15-4)
  command 'hfs' from deb hfsutils-tcltk (3.2.6-15build2)
Try: sudo apt install <deb name>
hadoop@aaronhowell-virtual-machine: /usr/local/hadoop$ ./bin/hdfs dfs -ls /user/h
adoop/ex4
Found 1 items
-rw-r--r-- 3 hadoop supergroup 0 2023-10-03 19:23 /user/hadoop/ex4/te
st.txt
hadoop@aaronhowell-virtual-machine: /usr/local/hadoop$ ./bin/hdfs dfs -ls /user/h
adoop/ex4
hadoop@aaronhowell-virtual-machine: /usr/local/hadoop$
```

程序提示删除，通过 shell 命令，可知该目录下没有任何东西，确已删除。

(7) 提供一个 HDFS 的目录的路径，对该目录进行创建和删除操作。创建目录时， 如果目录文件所在目录不存在则自动创建相应目录；删除目录时， 由用户指定当该目录不为空时是否还删除该目录；

①Shell 命令:

a. 按路径创建目录

```
Terminal File Edit View Search Terminal Help
hadoop@ubuntu:~$ cd /usr/local/hadoop
hadoop@ubuntu:/usr/local/hadoop$ ./sbin/start-dfs.sh
Starting namenodes on [localhost]
Starting datanodes
Starting secondary namenodes [ubuntu]
hadoop@ubuntu:/usr/local/hadoop$ ./bin/hdfs dfs -ls -R -h /
drwxr-xr-x - hadoop supergroup 0 2023-10-12 07:10 /fileTest
-rw-r--r-- 1 hadoop supergroup 5 2023-10-12 07:10 /fileTest/test.txt
drwxr-xr-x - hadoop supergroup 0 2023-10-12 07:57 /usr
drwxr-xr-x - hadoop supergroup 0 2023-10-12 07:57 /usr/local
drwxr-xr-x - hadoop supergroup 0 2023-10-12 08:08 /usr/local/dataFile
hadoop@ubuntu:/usr/local/hadoop$ ./bin/hdfs dfs -mkdir -p /usr/sample 创建目录
hadoop@ubuntu:/usr/local/hadoop$ ^C
hadoop@ubuntu:/usr/local/hadoop$ ./bin/hdfs dfs -ls -R -h /
drwxr-xr-x - hadoop supergroup 0 2023-10-12 07:10 /fileTest
-rw-r--r-- 1 hadoop supergroup 5 2023-10-12 07:10 /fileTest/test.txt
drwxr-xr-x - hadoop supergroup 0 2023-10-12 09:38 /usr
drwxr-xr-x - hadoop supergroup 0 2023-10-12 07:57 /usr/local
drwxr-xr-x - hadoop supergroup 0 2023-10-12 08:08 /usr/local/dataFile
drwxr-xr-x - hadoop supergroup 0 2023-10-12 09:38 /usr/sample 创建成功
hadoop@ubuntu:/usr/local/hadoop$
```

b. 新建目录文件

```
Terminal File Edit View Search Terminal Help
hadoop@ubuntu:~$ cd /usr/local/hadoop
hadoop@ubuntu:/usr/local/hadoop$ ./bin/hdfs dfs -ls -R -h /
drwxr-xr-x - hadoop supergroup 0 2023-10-12 07:10 /fileTest
-rw-r--r-- 1 hadoop supergroup 5 2023-10-12 07:10 /fileTest/test.txt
drwxr-xr-x - hadoop supergroup 0 2023-10-12 09:38 /usr
drwxr-xr-x - hadoop supergroup 0 2023-10-12 07:57 /usr/local
drwxr-xr-x - hadoop supergroup 0 2023-10-12 08:08 /usr/local/dataFile
drwxr-xr-x - hadoop supergroup 0 2023-10-12 09:38 /usr/sample
hadoop@ubuntu:/usr/local/hadoop$ ./bin/hdfs dfs -touchz /usr/sample/b.txt
hadoop@ubuntu:/usr/local/hadoop$ ./bin/hdfs dfs -ls -R -h /
drwxr-xr-x - hadoop supergroup 0 2023-10-12 07:10 /fileTest 新建文件夹内文件
-rw-r--r-- 1 hadoop supergroup 5 2023-10-12 07:10 /fileTest/test.txt
drwxr-xr-x - hadoop supergroup 0 2023-10-12 09:38 /usr
drwxr-xr-x - hadoop supergroup 0 2023-10-12 07:57 /usr/local
drwxr-xr-x - hadoop supergroup 0 2023-10-12 08:08 /usr/local/dataFile
drwxr-xr-x - hadoop supergroup 0 2023-10-12 09:44 /usr/sample
-rw-r--r-- 1 hadoop supergroup 0 2023-10-12 09:44 /usr/sample/b.txt
```

c. 测试删除目录，提示有文件，测试强制删除，删除成功

```
hadoop@ubuntu:/usr/local/hadoop$ ./bin/hdfs dfs -rmdir /usr/sample
rmdir: '/usr/sample': Directory is not empty
hadoop@ubuntu:/usr/local/hadoop$ ./bin/hdfs dfs -rm -R /usr/sample
Deleted /usr/sample
hadoop@ubuntu:/usr/local/hadoop$ ./bin/hdfs dfs -ls -R -h /
drwxr-xr-x - hadoop supergroup 0 2023-10-12 07:10 /fileTest
-rw-r--r-- 1 hadoop supergroup 5 2023-10-12 07:10 /fileTest/test.txt
drwxr-xr-x - hadoop supergroup 0 2023-10-12 09:45 /usr
drwxr-xr-x - hadoop supergroup 0 2023-10-12 07:57 /usr/local
drwxr-xr-x - hadoop supergroup 0 2023-10-12 08:08 /usr/local/dataFile
删除文件夹提示文件夹不空
强制删除
删除成功
```

②Java:

(方案一)

源代码:

```
import java.io.IOException;

import org.apache.hadoop.conf.Configuration;
import org.apache.hadoop.fs.FileSystem;
import org.apache.hadoop.fs.Path;
public class HdfsDirectoryManager {

    private FileSystem fs;

    public HdfsDirectoryManager() throws IOException {
        Configuration conf = new Configuration();
        conf.set("fs.defaultFS", "hdfs://localhost:9000");
        conf.set("fs.hdfs.impl", "org.apache.hadoop.hdfs.DistributedFileSystem");
        fs = FileSystem.get(conf);
    }

    public void createDirectory(String path) throws IOException {
        Path hdfsPath = new Path(path);
        if (!fs.exists(hdfsPath)) {
            fs.mkdirs(hdfsPath);
            System.out.println("Directory created: " + path);
        } else {
            System.out.println("Directory already exists: " + path);
        }
    }

    public void deleteDirectory(String path, boolean recursive) throws IOException {
        Path hdfsPath = new Path(path);
        if (fs.exists(hdfsPath)) {
            fs.delete(hdfsPath, recursive);
            System.out.println("Directory deleted: " + path);
        } else {
            System.out.println("Directory does not exist: " + path);
        }
    }

    public static void main(String[] args) throws IOException {
        HdfsDirectoryManager manager = new HdfsDirectoryManager();

        // 创建目录
        String directoryPath = "/user/hadoop/mydir";
        manager.createDirectory(directoryPath);

        // // 删除目录
        // boolean recursive = true; // 如果目录不为空, 也删除该目录
        // manager.deleteDirectory(directoryPath, recursive);

    }
}
```

实现结果：

a. 创建前

Browse Directory

Show entries

Search:

☐	Permission	Owner	Group	Size	Last Modified	Replication	Block Size	Name	
☐	-rw-r--r--	hadoop	supergroup	41 B	Oct 12 22:48	3	128 MB	file1.txt	

Showing 1 to 1 of 1 entries

Hadoop, 2019.

b. 创建后

Show entries

Search:

☐	Permission	Owner	Group	Size	Last Modified	Replication	Block Size	Name	
☐	-rw-r--r--	hadoop	supergroup	41 B	Oct 12 22:48	3	128 MB	file1.txt	
☐	drwxr-xr-x	hadoop	supergroup	0 B	Oct 13 00:03	0	0 B	mydir	

Showing 1 to 2 of 2 entries

（方案二）
源代码：

```
import org.apache.hadoop.conf.Configuration;
import org.apache.hadoop.fs.*;
import java.io.IOException;
import java.util.Scanner;

public class HDFSFileMakeOrRemove {

    public static void main(String[] args) {
        Configuration hdfsConfiguration = new Configuration();
        hdfsConfiguration.set("fs.default.name", "hdfs://localhost:9000");
        String hdfsDirectory = "/user/hadoop/ex4"; // HDFS 目录

        try (FileSystem fileSystem = FileSystem.get(hdfsConfiguration)) {
            if (!fileSystem.exists(new Path(hdfsDirectory)) || isHdfsDirectoryEmpty(fileSystem, hdfsDirectory)) {
                if (!fileSystem.exists(new Path(hdfsDirectory))) {
                    fileSystem.mkdirs(new Path(hdfsDirectory)); // 创建目录
                    System.out.println("创建目录: " + hdfsDirectory);
                } else {
                    removeHdfsDirectory(fileSystem, hdfsDirectory); // 删除目录
                    System.out.println("删除目录: " + hdfsDirectory);
                }
            } else {
                System.out.println("目录不为空, 不删除: " + hdfsDirectory);
            }
        } catch (Exception e) {
            e.printStackTrace();
        }
    }

    public static boolean isHdfsDirectoryEmpty(FileSystem fileSystem, String hdfsDirectory) {
        Path hdfsPath = new Path(hdfsDirectory);
        RemoteIterator<LocatedFileStatus> remoteIterator = fileSystem.listFiles(hdfsPath, true);
        return !remoteIterator.hasNext();
    }

    public static boolean removeHdfsDirectory(FileSystem fileSystem, String hdfsDirectory) {
        Path hdfsPath = new Path(hdfsDirectory);
        boolean result = fileSystem.delete(hdfsPath, true);
        return result;
    }

    public static boolean askUserToDeleteHdfsDirectory() {
        Scanner scanner = new Scanner(System.in);
        System.out.print("目录不为空, 是否删除 (Y/N)? ");
        String choice = scanner.nextLine().trim().toLowerCase();
        return choice.equals("y");
    }
}
```

实现结果:

a.

```
check: localhostTrusted = false, remoteHostTrusted = false
hadoop@aaronhowell-virtual-machine:/usr/local/hadoop$ hdfs dfs -ls /user/hadoop/ex4
Command 'hdfs' not found, did you mean:
  command 'hdfsls' from deb hdf4-tools (4.2.15-4)
  command 'hfs' from deb hfsutils-tcltk (3.2.6-15build2)
Try: sudo apt install <deb name>
hadoop@aaronhowell-virtual-machine:/usr/local/hadoop$ ./bin/hdfs dfs -ls /user/hadoop/ex4
Found 1 items
-rw-r--r--  3 hadoop supergroup          0 2023-10-03 19:23 /user/hadoop/ex4/test.txt
hadoop@aaronhowell-virtual-machine:/usr/local/hadoop$ ./bin/hdfs dfs -ls /user/hadoop/ex4
hadoop@aaronhowell-virtual-machine:/usr/local/hadoop$ ./bin/hdfs dfs -ls /user/hadoop/ex4
hadoop@aaronhowell-virtual-machine:/usr/local/hadoop$ ./bin/hdfs dfs -touchz /user/hadoop/ex4/test.txt
hadoop@aaronhowell-virtual-machine:/usr/local/hadoop$ ./bin/hdfs dfs -ls /user/hadoop/ex4
Found 1 items
-rw-r--r--  1 hadoop supergroup          0 2023-10-12 18:17 /user/hadoop/ex4/test.txt
hadoop@aaronhowell-virtual-machine:/usr/local/hadoop$
```

b. 目录下创建一个 test.txt 然后运行程序，可选择删除或是不删除

```
目录不为空，是否删除 (Y/N)? N
目录不为空，不删除: /user/hadoop/ex4

目录不为空，是否删除 (Y/N)? Y
删除目录: /user/hadoop/ex4
```

c. 选择删除后，确认已删除

```
Command 'hdfs' not found, did you mean:
  command 'hdfsls' from deb hdf4-tools (4.2.15-4)
  command 'hfs' from deb hfsutils-tcltk (3.2.6-15build2)
Try: sudo apt install <deb name>
hadoop@aaronhowell-virtual-machine:/usr/local/hadoop$ ./bin/hdfs dfs -ls /user/hadoop/ex4
Found 1 items
-rw-r--r--  3 hadoop supergroup          0 2023-10-03 19:23 /user/hadoop/ex4/test.txt
hadoop@aaronhowell-virtual-machine:/usr/local/hadoop$ ./bin/hdfs dfs -ls /user/hadoop/ex4
hadoop@aaronhowell-virtual-machine:/usr/local/hadoop$ ./bin/hdfs dfs -ls /user/hadoop/ex4
hadoop@aaronhowell-virtual-machine:/usr/local/hadoop$ ./bin/hdfs dfs -touchz /user/hadoop/ex4/test.txt
hadoop@aaronhowell-virtual-machine:/usr/local/hadoop$ ./bin/hdfs dfs -ls /user/hadoop/ex4
Found 1 items
-rw-r--r--  1 hadoop supergroup          0 2023-10-12 18:17 /user/hadoop/ex4/test.txt
hadoop@aaronhowell-virtual-machine:/usr/local/hadoop$ ./bin/hdfs dfs -ls /user/hadoop/ex4
ls: '/user/hadoop/ex4': No such file or directory
hadoop@aaronhowell-virtual-machine:/usr/local/hadoop$
```

d. 再次运行代码，成功创建目录

```
log4j:WARN No appenders could be found for logger
log4j:WARN Please initialize the log4j system
log4j:WARN See http://logging.apache.org/log4j/faq.html#no-appender
创建目录: /user/hadoop/ex4
```

```
command 'hfs' from deb hfsutils-tcltk (3.2.6-15build2)
Try: sudo apt install <deb name>
hadoop@aaronhowell-virtual-machine:/usr/local/hadoop$ ./bin/hdfs dfs -ls /user/hadoop/ex4
Found 1 items
-rw-r--r-- 3 hadoop supergroup 0 2023-10-03 19:23 /user/hadoop/ex4/test.txt
hadoop@aaronhowell-virtual-machine:/usr/local/hadoop$ ./bin/hdfs dfs -ls /user/hadoop/ex4
hadoop@aaronhowell-virtual-machine:/usr/local/hadoop$ ./bin/hdfs dfs -touchz /user/hadoop/ex4/test.txt
hadoop@aaronhowell-virtual-machine:/usr/local/hadoop$ ./bin/hdfs dfs -ls /user/hadoop/ex4
Found 1 items
-rw-r--r-- 1 hadoop supergroup 0 2023-10-12 18:17 /user/hadoop/ex4/test.txt
hadoop@aaronhowell-virtual-machine:/usr/local/hadoop$ ./bin/hdfs dfs -ls /user/hadoop/ex4
ls: '/user/hadoop/ex4': No such file or directory
hadoop@aaronhowell-virtual-machine:/usr/local/hadoop$ ./bin/hdfs dfs -ls /user/hadoop/ex4
hadoop@aaronhowell-virtual-machine:/usr/local/hadoop$
```


(8) 向 HDFS 中指定的文件追加内容，由用户指定内容追加到原有文件的开头或结尾；

①Shell 命令：

a. 向指定文件末尾添加指定内容

```
hadoop@ubuntu:~$ cd /usr/local/hadoop
hadoop@ubuntu:/usr/local/hadoop$ ./bin/hdfs dfs -cat /fileTest/test.txt
2023-10-12 09:53:24,109 INFO sasl.SaslDataTransferClient: SASL encryption trust check: localhostTrusted = false, remoteHostTrusted = false
Test 原内容
hadoop@ubuntu:/usr/local/hadoop$ ./bin/hdfs dfs -appendToFile test.txt /fileTest/test.txt
2023-10-12 09:53:36,888 INFO sasl.SaslDataTransferClient: SASL encryption trust check: localhostTrusted = false, remoteHostTrusted = false
hadoop@ubuntu:/usr/local/hadoop$ ^C
hadoop@ubuntu:/usr/local/hadoop$ ./bin/hdfs dfs -cat /fileTest/test.txt 向指定文件添加指定内容
2023-10-12 09:53:51,241 INFO sasl.SaslDataTransferClient: SASL encryption trust check: localhostTrusted = false, remoteHostTrusted = false
Test 添加成功
Test
hadoop@ubuntu:/usr/local/hadoop$
```

b. 将 HDFS 文件下载至本地




```
hadoop@ubuntu:~$ cd /usr/local/hadoop
hadoop@ubuntu:/usr/local/hadoop$ ./bin/hdfs dfs -cat /fileTest/test.txt
2023-10-12 10:01:52,348 INFO sasl.SaslDataTransferClient: SASL encryption trust
check: localHostTrusted = false, remoteHostTrusted = false
Test
Test
hadoop@ubuntu:/usr/local/hadoop$ ./bin/hdfs dfs -get /fileTest/test.txt
get: 'test.txt': File exists
hadoop@ubuntu:/usr/local/hadoop$ cat /fileTest/test.txt >> local.txt
cat: /fileTest/test.txt: 没有那个文件或目录
hadoop@ubuntu:/usr/local/hadoop$ cat test.txt >> local.txt
hadoop@ubuntu:/usr/local/hadoop$
```

文件内容

将文件读取到本地local.txt中


c. 修改下载的本地图容



```
File Edit View Search Tools Documents Help
Open [icon]
Nice Try
```

修改本地文件内容

d. 上传并覆盖



```
hadoop@ubuntu:~$ cd /usr/local/hadoop
hadoop@ubuntu:/usr/local/hadoop$ ./bin/hdfs dfs -copyFromLocal -f local.txt /fileTest/test.txt
2023-10-12 10:06:00,232 INFO sasl.SaslDataTransferClient: SASL encryption trust check: localHostTrusted = false, remoteHostTrusted = false
hadoop@ubuntu:/usr/local/hadoop$ ./bin/hdfs dfs -cat /fileTest/test.txt
2023-10-12 10:06:21,363 INFO sasl.SaslDataTransferClient: SASL encryption trust check: localHostTrusted = false, remoteHostTrusted = false
Nice Try
hadoop@ubuntu:/usr/local/hadoop$
```

上传成功

将修改后的文件覆盖上传

②Java:

(方案一)

源代码:

```
import org.apache.hadoop.conf.Configuration;
import org.apache.hadoop.fs.FSDataInputStream;
import org.apache.hadoop.fs.FSDataOutputStream;
import org.apache.hadoop.fs.FileSystem;
import org.apache.hadoop.fs.Path;

import java.io.ByteArrayOutputStream;
import java.io.IOException;

public class HdfsFileManager {

    private FileSystem fs;

    public HdfsFileManager() throws IOException {
        Configuration conf = new Configuration();
        conf.set("fs.defaultFS", "hdfs://localhost:9000");
        conf.set("fs.hdfs.impl", "org.apache.hadoop.hdfs.DistributedFileSystem");
        fs = FileSystem.get(conf);
    }

    public void appendToFile(String path, String content, boolean appendToEnd) throws IOException {
        Path hdfsPath = new Path(path);
        if (!fs.exists(hdfsPath)) {
            System.out.println("File does not exist: " + path);
            return;
        }

        FSDataOutputStream outputStream;
        if (appendToEnd) {
            outputStream = fs.append(hdfsPath);
            outputStream.writeBytes(content);
        } else {
            // Hadoop does not support prepending to a file directly.
            // You need to read the original content, then write the new content and the original content.
            FSDataInputStream inputStream = fs.open(hdfsPath);
            ByteArrayOutputStream byteArrayOutputStream = new ByteArrayOutputStream();
            byte[] buffer = new byte[1024];
            int length;
            while ((length = inputStream.read(buffer)) != -1) {
                byteArrayOutputStream.write(buffer, 0, length);
            }
            String originalContent = byteArrayOutputStream.toString();
            inputStream.close();

            outputStream = fs.create(hdfsPath, true); // overwrite the file
            outputStream.writeBytes(content + originalContent);
        }
        outputStream.close();
    }

    public static void main(String[] args) throws IOException {
        HdfsFileManager manager = new HdfsFileManager();

        // 追加内容到文件的末尾
        String filePath = "/user/hadoop/file1.txt";
        manager.appendToFile(filePath, "New content at the end of the file.", true);


        // 追加内容到文件的开头
        String filePath = "/user/hadoop/file1.txt";
        manager.appendToFile(filePath, "New modified content at the beginning of the file.", false);
    }
}
```

实现结果：


a. 原始文件



b. 增加在末尾



c. 增加在开头



（方案二）

源代码：

```
import org.apache.hadoop.conf.Configuration;
import org.apache.hadoop.fs.*;
import java.io.BufferedWriter;
import java.io.BufferedReader;
import java.io.OutputStreamWriter;
import java.io.IOException;
import java.io.InputStreamReader;
import java.util.Scanner;

public class HDFSFileAppend {

    public static void main(String[] args) {
        Configuration hdfsConfiguration = new Configuration();
        hdfsConfiguration.set("fs.default.name", "hdfs://localhost:9000");
        String hdfsFilePath = "/user/hadoop/ex4/test.txt"; // HDFS 文件路径

        try (FileSystem fileSystem = FileSystem.get(hdfsConfiguration)) {
            if (fileSystem.exists(new Path(hdfsFilePath)) && appendContentToFile(fileSystem,
                System.out.println("内容已追加到文件: " + hdfsFilePath);
            } else {
                System.out.println("文件不存在或操作取消: " + hdfsFilePath);
            }
        } catch (Exception e) {
            e.printStackTrace();
        }
    }

    public static boolean appendContentToFile(FileSystem fileSystem, String hdfsFilePath) {
        Scanner scanner = new Scanner(System.in);
        System.out.print("是否追加到文件开头 (Y/N)? ");
        String choice = scanner.nextLine().trim().toLowerCase();

        if (choice.equals("y")) {
            return appendContent(fileSystem, hdfsFilePath, true);
        } else if (choice.equals("n")) {
            return appendContent(fileSystem, hdfsFilePath, false);
        } else {
            System.out.println("无效选择, 操作取消。");
            return false;
        }
    }

    public static boolean appendContent(FileSystem fileSystem, String hdfsFilePath, boolean a
        try {
            String content = getUserInputContent();
            FSDataOutputStream outputStream = fileSystem.append(new Path(hdfsFilePath));
            BufferedWriter writer = new BufferedWriter(new OutputStreamWriter(outputStream));
            if (appendToBeginning) {
                writer.close();
                String existingContent = "";
                Path hdfsPath = new Path(hdfsFilePath);
                FSDataInputStream inputStream = fileSystem.open(hdfsPath);
                BufferedReader reader = new BufferedReader(new InputStreamReader(inputStream));
                String line;
                while ((line = reader.readLine()) != null) {
                    existingContent += line + "\n";
                }
                reader.close();

                // 合并原内容和新内容
                content = content + existingContent;

                // 清空源文件
                FSDataOutputStream clearOutputStream = fileSystem.create(hdfsPath, true);
                BufferedWriter clearWriter = new BufferedWriter(new OutputStreamWriter(clearOutputStream));
                clearWriter.write("");
                clearWriter.close();

                // 写入合并的字符串
                FSDataOutputStream outputStream1 = fileSystem.append(hdfsPath);
                BufferedWriter writer1 = new BufferedWriter(new OutputStreamWriter(outputStream1));
                writer1.write(content);
                writer1.close();
            } else {
                writer.append(content);
                writer.close();
            }

            return true;
        } catch (IOException e) {
            e.printStackTrace();
            return false;
        }
    }

    public static String getUserInputContent() {
        Scanner scanner = new Scanner(System.in);
        System.out.print("请输入要追加的内容: ");
        return scanner.nextLine();
    }
}
```

实现结果：

a. 初始文件：test.txt 中，原本包含的文字为 something

b. 增加在开头

```
<terminated> HDFSFileAppend [Java Application] /usr
log4j:WARN No appenders could be found for l
log4j:WARN Please initialize the log4j syste
log4j:WARN See http://logging.apache.org/log
是否追加到文件开头 (Y/N)? Y
请输入要追加的内容: Begin
内容已追加到文件: /user/hadoop/ex4/test.txt
```

```
hadoop@aaronhowell-virtual-machine:/usr/local/hadoop$ ./bin/hdfs dfs -cat /user/
hadoop/ex4/test.txt
2023-10-12 19:06:34,074 INFO sasl.SaslDataTransferClient: SASL encryption trust
check: localhostTrusted = false, remoteHostTrusted = false
BeginSomething
```

c. 增加在末尾

```
hadoop@aaronhowell-virtual-machine:/usr/local/hadoop$ ./bin/hdfs dfs -cat /user/
hadoop/ex4/test.txt
2023-10-12 19:38:07,000 INFO sasl.SaslDataTransferClient: SASL encryption trust
check: localhostTrusted = false, remoteHostTrusted = false
BeginSomethingEndinghadoop@aaronhowell-virtual-machine:/usr/local/hadoop$
```

(9) 删除 HDFS 中指定的文件；

①Shell 命令：

删除指定文件

```
Terminal File Edit View Search Terminal Help
hadoop@ubuntu:~$ cd /usr/local/hadoop
hadoop@ubuntu:/usr/local/hadoop$ ./bin/hdfs dfs -ls -R -h /
drwxr-xr-x - hadoop supergroup 0 2023-10-12 10:06 /fileTest
-rw-r--r-- 1 hadoop supergroup 9 2023-10-12 10:06 /fileTest/test.txt
-rw-r--r-- 1 hadoop supergroup 5 2023-10-12 09:52 /fileTest/text.txt
drwxr-xr-x - hadoop supergroup 0 2023-10-12 09:45 /usr
drwxr-xr-x - hadoop supergroup 0 2023-10-12 07:57 /usr/local
drwxr-xr-x - hadoop supergroup 0 2023-10-12 08:08 /usr/local/dataFile
hadoop@ubuntu:/usr/local/hadoop$ ./bin/hdfs dfs -rm -r /fileTest/text.txt
Deleted /fileTest/text.txt
hadoop@ubuntu:/usr/local/hadoop$ ./bin/hdfs dfs -ls -R -h /
drwxr-xr-x - hadoop supergroup 0 2023-10-12 10:09 /fileTest
-rw-r--r-- 1 hadoop supergroup 9 2023-10-12 10:06 /fileTest/test.txt
drwxr-xr-x - hadoop supergroup 0 2023-10-12 09:45 /usr
drwxr-xr-x - hadoop supergroup 0 2023-10-12 07:57 /usr/local
drwxr-xr-x - hadoop supergroup 0 2023-10-12 08:08 /usr/local/dataFile
hadoop@ubuntu:/usr/local/hadoop$
```

②Java:

源代码:

```
import org.apache.hadoop.conf.Configuration;
import org.apache.hadoop.fs.FileSystem;
import org.apache.hadoop.fs.Path;

import java.io.IOException;

public class HdfsFileManager9 {

    private FileSystem fs;

    public HdfsFileManager9() throws IOException {
        Configuration conf = new Configuration();
        conf.set("fs.defaultFS", "hdfs://localhost:9000");
        conf.set("fs.hdfs.impl", "org.apache.hadoop.hdfs.DistributedFileSystem");
        fs = FileSystem.get(conf);
    }

    public void deleteFile(String path) throws IOException {
        Path hdfsPath = new Path(path);
        if (fs.exists(hdfsPath)) {
            fs.delete(hdfsPath, false);
            System.out.println("File deleted: " + path);
        } else {
            System.out.println("File does not exist: " + path);
        }
    }

    public static void main(String[] args) throws IOException {
        HdfsFileManager9 manager = new HdfsFileManager9();

        // 删除文件
        String filePath = "/user/hadoop/file3.txt";
        manager.deleteFile(filePath);
    }
}
```

实现效果:

a. 删除前

Browse Directory

/user/hadoop

Go!

Show

25

entries

Search:

☐	Permission	Owner	Group	Size	Last Modified	Replication	Block Size	Name	
☐	-rw-r--r--	hadoop	supergroup	41 B	Oct 12 22:48	3	128 MB	file1.txt	
☐	-rw-r--r--	hadoop	supergroup	19 B	Oct 12 23:26	1	128 MB	file3.txt	


Showing 1 to 2 of 2 entries

Previous


1

Next

b. 运行代码




c. 删除后



(10) 删除 HDFS 中指定的目录，由用户指定目录中如果存在文件时是否删除目录；

①Shell 命令：

删除指定目录，不为空时提示



```
hadoop@ubuntu:~$ cd /usr/local/hadoop
hadoop@ubuntu:/usr/local/hadoop$ ./bin/hdfs dfs -ls -R -h /
drwxr-xr-x  - hadoop supergroup      0 2023-10-12 10:09 /fileTest
-rw-r--r--  1 hadoop supergroup      9 2023-10-12 10:06 /fileTest/test.txt
drwxr-xr-x  - hadoop supergroup      0 2023-10-12 09:45 /usr
drwxr-xr-x  - hadoop supergroup      0 2023-10-12 07:57 /usr/local
drwxr-xr-x  - hadoop supergroup      0 2023-10-12 08:08 /usr/local/dataFile
hadoop@ubuntu:/usr/local/hadoop$ ./bin/hdfs dfs -rmrmdir /fileTest
rmrmdir: `/fileTest': Directory is not empty
hadoop@ubuntu:/usr/local/hadoop$
```

②Java:

(方案一)

源代码:

```
import java.io.IOException;

import org.apache.hadoop.conf.Configuration;
import org.apache.hadoop.fs.FileSystem;
import org.apache.hadoop.fs.Path;
public class HdfsDirectoryManager10 {

    private FileSystem fs;

    public HdfsDirectoryManager10() throws IOException {
        Configuration conf = new Configuration();
        conf.set("fs.defaultFS", "hdfs://localhost:9000");
        conf.set("fs.hdfs.impl", "org.apache.hadoop.hdfs.DistributedFileSystem");
        fs = FileSystem.get(conf);
    }

    public void deleteDirectory(String path, boolean recursive) throws IOException {
        Path hdfsPath = new Path(path);
        if (fs.exists(hdfsPath)) {
            fs.delete(hdfsPath, recursive);
            System.out.println("Directory deleted: " + path);
        } else {
            System.out.println("Directory does not exist: " + path);
        }
    }

    public static void main(String[] args) throws IOException {
        HdfsDirectoryManager manager = new HdfsDirectoryManager();

        // 删除目录
        String directoryPath = "/user/hadoop/mydir";
        boolean recursive = true; // 如果目录不为空, 也删除该目录
        manager.deleteDirectory(directoryPath, recursive);
    }
}
```

运行结果:

删除前:

/user/hadoop/mydir

Go!

Show

25

entries

Search:

☐	Permission	Owner	Group	Size	Last Modified	Replication	Block Size	Name	
☐	-rw-r--r--	hadoop	supergroup	41 B	Oct 12 22:48	3	128 MB	file1.txt	

Showing 1 to 1 of 1 entries

Previous

1

Next

删除后:

Browse Directory

Path does not exist on HDFS or WebHDFS is disabled. Please check your path or enable WebHDFS

Hadoop, 2019.

(方案二)

源代码:

```
public static void deleteDirectory(Configuration conf, String filePath) throws IOException {
    FileSystem fs = FileSystem.get(conf);
    Path path = new Path(filePath);
    FileStatus[] status = fs.listStatus(path);
    if(status.length > 0) {
        System.out.println("该目录中存在文件, 是否继续删除Y/N");
        Scanner cin = new Scanner(System.in);
        String flag = cin.next();
        if(flag.equals("Y")) {
            fs.delete(path, true);
            System.out.println("目录已删除.");
        } else {
            System.out.println("用户取消删除.");
        }
    } else {
        fs.delete(path, true);
        System.out.println("目录已删除.");
    }
    fs.close();
}

public static void main(String[] args) throws IOException, InterruptedException, URISyntaxException {
    Scanner cin = new Scanner(System.in);
    Configuration conf = new Configuration();
    conf.set("fs.defaultFS", "hdfs://localhost:9000");
    conf.set("dfs.client.block.write.replace-datanode-on-failure.enable", "true");
    conf.set("dfs.client.block.write.replace-datanode-on-failure.policy", "NEVER");
    conf.set("dfs.replication", "1");
    String dirPath = "test/hadoop/aaa.txt";
    exp10.createFile(conf, dirPath);
    exp10.deleteDirectory(conf, "test");
    System.out.println("end.");
}
```

实现结果:

Problems @ Javadoc Declaration Console

<terminated> exp10 [Java Application] /usr/lib/jvm/jdk1.8.0_162/bin/java (Oct 12, 2023, 2:33:40 AM)

log4j:WARN No appenders could be found for logger (org.apache.hadoop.util.Shell).

log4j:WARN Please initialize the log4j system properly.

log4j:WARN See <http://logging.apache.org/log4j/1.2/faq.html#noconfig> for more info.

文件创建成功: test/hadoop/aaa.txt

该目录中存在文件, 是否继续删除Y/N

Y


目录已删除.

end.

(11) 在 HDFS 中，将文件从源路径移动到目的路径。

①Shell 命令：

移动指定文件至指定路径

A terminal window titled "Terminal" with a menu bar (File, Edit, View, Search, Terminal, Help). The user is in the directory /usr/local/hadoop. They run 'hadoop@ubuntu:~\$ cd /usr/local/hadoop' and then 'hadoop@ubuntu:/usr/local/hadoop\$./bin/hdfs dfs -ls -R -h /'. The output shows a directory tree with /usr/local/dataFile highlighted in green. Then they run 'hadoop@ubuntu:/usr/local/hadoop\$./bin/hdfs dfs -mv /fileTest/test.txt /usr/local/dataFile' and 'hadoop@ubuntu:/usr/local/hadoop\$./bin/hdfs dfs -ls -R -h /'. The output shows the file has been moved to /usr/local/dataFile/test.txt, which is also highlighted in green. A green box highlights the command and the final output line. A green arrow points from the text "移动文件至目标路径" to the command. A green box highlights the final output line, and a green arrow points from the text "移动成功" to it.

```
hadoop@ubuntu:~$ cd /usr/local/hadoop
hadoop@ubuntu:/usr/local/hadoop$ ./bin/hdfs dfs -ls -R -h /
drwxr-xr-x  - hadoop supergroup      0 2023-10-12 10:09 /fileTest
-rw-r--r--  1 hadoop supergroup      9 2023-10-12 10:06 /fileTest/test.txt
drwxr-xr-x  - hadoop supergroup      0 2023-10-12 09:45 /usr
drwxr-xr-x  - hadoop supergroup      0 2023-10-12 07:57 /usr/local
drwxr-xr-x  - hadoop supergroup      0 2023-10-12 08:08 /usr/local/dataFile
hadoop@ubuntu:/usr/local/hadoop$ ./bin/hdfs dfs -mv /fileTest/test.txt /usr/local/dataFile
hadoop@ubuntu:/usr/local/hadoop$ ./bin/hdfs dfs -ls -R -h /
drwxr-xr-x  - hadoop supergroup      0 2023-10-12 10:23 /fileTest
drwxr-xr-x  - hadoop supergroup      0 2023-10-12 09:45 /usr
drwxr-xr-x  - hadoop supergroup      0 2023-10-12 07:57 /usr/local
drwxr-xr-x  - hadoop supergroup      0 2023-10-12 10:23 /usr/local/dataFile
-rw-r--r--  1 hadoop supergroup      9 2023-10-12 10:06 /usr/local/dataFile/test.txt
hadoop@ubuntu:/usr/local/hadoop$
```

②Java:

(方案一)

源代码:

```
import org.apache.hadoop.conf.Configuration;
import org.apache.hadoop.fs.FileSystem;
import org.apache.hadoop.fs.Path;

import java.io.IOException;

public class HdfsFileManager11 {

    private FileSystem fs;

    public HdfsFileManager11() throws IOException {
        Configuration conf = new Configuration();
        conf.set("fs.defaultFS", "hdfs://localhost:9000");
        conf.set("fs.hdfs.impl", "org.apache.hadoop.hdfs.DistributedFileSystem");
        fs = FileSystem.get(conf);
    }

    public void moveFile(String sourcePath, String destinationPath) throws IOException {
        Path srcPath = new Path(sourcePath);
        Path dstPath = new Path(destinationPath);
        if (!fs.exists(srcPath)) {
            System.out.println("Source file does not exist: " + sourcePath);
            return;
        }
        if (fs.exists(dstPath)) {
            System.out.println("Destination file already exists: " + destinationPath);
            return;
        }
        boolean isMoved = fs.rename(srcPath, dstPath);
        if (isMoved) {
            System.out.println("File moved successfully from " + sourcePath + " to " + destinationPath);
        } else {
            System.out.println("Failed to move file from " + sourcePath + " to " + destinationPath);
        }
    }

    public static void main(String[] args) throws IOException {
        HdfsFileManager11 manager = new HdfsFileManager11();

        // 移动文件
        String sourceFilePath = "/user/hadoop/file1.txt";
        String destinationFilePath = "/user/hadoop/mydir/myfile.txt";
        manager.moveFile(sourceFilePath, destinationFilePath);
    }
}
```

实现结果：

a. 移动前

hadoop

Overview

Datanodes

Datanode Volume Failures

Snapshot

Startup Progress

Utilities

Browse Directory

/user/hadoop

Go!

Show

25

entries

Search:

☐	Permission	Owner	Group	Size	Last Modified	Replication	Block Size	Name	
☐	-rw-r--r--	hadoop	supergroup	41 B	Oct 12 22:48	3	128 MB	file1.txt	
☐	drwxr-xr-x	hadoop	supergroup	0 B	Oct 13 00:03	0	0 B	mydir	

Showing 1 to 2 of 2 entries

Previous

1

Next

Hadoop, 2019.

b. 移动后

/user/hadoop/mydir

Go!

Show

25

entries

Search:

☐	Permission	Owner	Group	Size	Last Modified	Replication	Block Size	Name	
☐	-rw-r--r--	hadoop	supergroup	41 B	Oct 12 22:48	3	128 MB	file1.txt	

Showing 1 to 1 of 1 entries

Previous

1

Next

(方案二)

源代码：

```
public static void moveFile(Configuration conf, String srcPath, String dirPath) throws IOException {
    FileSystem fs = FileSystem.get(conf);
    if(fs.exists(new Path(dirPath))) {
        System.out.println("文件被占用。");
        return;
    }
    if(fs.rename(new Path(srcPath), new Path(dirPath))) {
        System.out.println("文件移动成功。");
    } else {
        System.out.println("文件移动失败。");
    }
}
```

a. 文件移动失败

```
public static void main(String[] args) throws IOException, InterruptedException, URISyntaxException {
    Scanner cin = new Scanner(System.in);
    Configuration conf = new Configuration();
    conf.set("fs.defaultFS", "hdfs://localhost:9000");
    conf.set("dfs.client.block.write.replace-datanode-on-failure.enable", "true");
    conf.set("dfs.client.block.write.replace-datanode-on-failure.policy", "NEVER");
    conf.set("dfs.replication", "1");
    String filePath = "hadoop.txt";
    exp10.moveFile(conf, filePath, "newHadoop.txt");
}
```

b. 文件处于被占用状态


```
public static void main(String[] args) throws IOException, InterruptedException, URISyntaxException {
    Scanner cin = new Scanner(System.in);
    Configuration conf = new Configuration();
    conf.set("fs.defaultFS", "hdfs://localhost:9000");
    conf.set("dfs.client.block.write.replace-datanode-on-failure.enable", "true");
    conf.set("dfs.client.block.write.replace-datanode-on-failure.policy", "NEVER");
    conf.set("dfs.replication", "1");
    String filePath = "/user/hadoop/hadoop.txt";
    String dirPath = "/user/hadoop/data.txt";
    exp10.moveFile(conf, filePath, dirPath);
}
}
```

c. 文件移动成功

```
public static void main(String[] args) throws IOException, InterruptedException, URISyntaxException {
    Scanner cin = new Scanner(System.in);
    Configuration conf = new Configuration();
    conf.set("fs.defaultFS", "hdfs://localhost:9000");
    conf.set("dfs.client.block.write.replace-datanode-on-failure.enable", "true");
    conf.set("dfs.client.block.write.replace-datanode-on-failure.policy", "NEVER");
    conf.set("dfs.replication", "1");
    String filePath = "/user/hadoop/hadoop.txt";
    exp10.moveFile(conf, filePath, "newHadoop.txt");
}
}
```


实现结果:

a. 文件移动失败




```
<terminated> exp10 [Java Application] /usr/lib/jvm/jdk1.8.0_162/bin/java (Oct 12, 2023, 2:37:40 AM)
log4j:WARN No appenders could be found for logger (org.apache.hadoop.util.Shell).
log4j:WARN Please initialize the log4j system properly.
log4j:WARN See http://logging.apache.org/log4j/1.2/faq.html#noconfig for more info.
文件移动失败。
```

b. 文件处于被占用状态



```
<terminated> exp10 [Java Application] /usr/lib/jvm/jdk1.8.0_162/bin/java (Oct 12, 2023, 9:32:14 AM)
log4j:WARN No appenders could be found for logger (org.apache.hadoop.util.Shell).
log4j:WARN Please initialize the log4j system properly.
log4j:WARN See http://logging.apache.org/log4j/1.2/faq.html#noconfig for more info.
文件被占用。
```

c. 文件移动成功



```
<terminated> exp10 [Java Application] /usr/lib/jvm/jdk1.8.0_162/bin/java (Oct 12, 2023, 9:35:27 AM)
log4j:WARN No appenders could be found for logger (org.apache.hadoop.util.Shell).
log4j:WARN Please initialize the log4j system properly.
log4j:WARN See http://logging.apache.org/log4j/1.2/faq.html#noconfig for more info.
文件移动成功。
```

2. 编程实现一个类“MyFSDataInputStream”,该类继承”org.apache.hadoop.fs.FSDataInputStream”,要求:实现按行读取 HDFS 中指定文件的方法 “readLine()”,如果读到文件末尾,则返回空,否则返回文件一行的文本。


(方案一)

源代码:

```
import java.io.BufferedReader;

public class MyFSDataInputStream {
    public static void main(String[] args) {
        try {
            Configuration conf = new Configuration();
            conf.set("fs.defaultFS", "hdfs://localhost:9000");
            conf.set("fs.hdfs.impl", "org.apache.hadoop.hdfs.DistributedFileSystem");
            FileSystem fs = FileSystem.get(conf);
            Path file = new Path("/user/hadoop/file1.txt");
            FSDataInputStream getIt = fs.open(file);
            BufferedReader d = new BufferedReader(new InputStreamReader(getIt));
            String content = d.readLine(); //读取文件一行
            if(content != null) {
                System.out.println(content);
            }
            else {
                System.out.println("this is the end of the file");
            }
            d.close(); //关闭文件
            fs.close(); //关闭hdfs
        } catch (Exception e) {
            e.printStackTrace();
        }
    }
}
```

实现结果:



(方案二)


源代码:

```

public static String readline(BufferedReader br) throws IOException {
    char[] data = new char[1024];
    int read = -1;
    int off = 0;
    // 循环执行时, br 每次会从上一次读取结束的位置继续读取
    // 因此该函数里, off 每次都从0开始
    while ( (read = br.read(data, off, 1)) != -1 ) {
        if (String.valueOf(data[off]).equals("\n") ) {
            off += 1;
            break;
        }
        off += 1;
    }

    if (off > 0) {
        return String.valueOf(data);
    } else {
        return null;
    }
}

```




```

MergeFile.java  exp10.java  MyFSDataInputStream.java
* 读取文件内容
*/
public static void cat(Configuration conf, String remoteFilePath) throws IOException {
    FileSystem fs = FileSystem.get(conf);
    Path remotePath = new Path(remoteFilePath);
    FSDataInputStream in = fs.open(remotePath);
    BufferedReader br = new BufferedReader(new InputStreamReader(in));
    String line = null;
    while ( (line = MyFSDataInputStream.readline(br)) != null ) {
        System.out.println(line);
    }
    br.close();
    in.close();
    fs.close();
}

/**
 * 主函数
 */
public static void main(String[] args) {
    Configuration conf = new Configuration();
    conf.set("fs.defaultFS", "hdfs://localhost:9000");
    String remoteFilePath = "/user/hadoop/data.txt";
    try {
        MyFSDataInputStream.cat(conf, remoteFilePath);
    } catch (Exception e) {
        e.printStackTrace();
    }
}
}

```

实现结果:



```

Problems  @ Javadoc  Declaration  Console
<terminated> MyFSDataInputStream [Java Application] /usr/lib/jvm/jdk1.8.0_162/bin/java (Oct 12, 2023, 5:26:19 AM)
log4j:WARN No appenders could be found for logger (org.apache.hadoop.util.Shell).
log4j:WARN Please initialize the log4j system properly.
log4j:WARN See http://logging.apache.org/log4j/1.2/faq.html#noconfig for more info.
this is data.txt

```

3. 查看 Java 帮助手册或其它资料，用 "java.net.URL" 和 "org.apache.hadoop.fs.FsURLStreamHandlerFactory" 编程完成输出 HDFS 中指定文件的文本到终端中。

源代码：


```
import org.apache.hadoop.conf.Configuration;
import org.apache.hadoop.fs.FsURLStreamHandlerFactory;
import java.io.BufferedReader;
import java.io.InputStreamReader;
import java.net.URL;

public class ReadFile {

    static {
        URL.setURLStreamHandlerFactory(new FsURLStreamHandlerFactory());
    }

    public static void main(String[] args) throws Exception {
        String hdfsFilePath = "hdfs://localhost:9000/user/hadoop/file1.txt";
        BufferedReader reader = null;
        try {
            URL url = new URL(hdfsFilePath);
            reader = new BufferedReader(new InputStreamReader(url.openStream()));
            String line;
            while ((line = reader.readLine()) != null) {
                System.out.println(line);
            }
        } finally {
            if (reader != null) {
                reader.close();
            }
        }
    }
}
```

实现结果：



```
<terminated> ReadFile [Java Application] /usr/lib/jvm/jdk1.8.0_162/bin/java (Oct 13, 2023, 12:32:33 AM)
log4j:WARN No appenders could be found for logger (org.apache.hadoop.fs.FileSystem).
log4j:WARN Please initialize the log4j system properly.
log4j:WARN See http://logging.apache.org/log4j/1.2/faq.html#noconfig for more info.
New modified content at the beginning of the file.New content at the beginning of the file.
```

五、 实验结果

1. 使用 Java 编程语言和 Shell 命令实现 HDFS 操作

(1) 上传文件到 HDFS: 通过编程实现了将本地文本文件上传到 HDFS 的功能。用户可以选择是追加到原有文件末尾还是覆盖原有文件;

(2) 下载文件: 编程实现了从 HDFS 中下载指定文件到本地, 并在本地文件名与要下载的文件名相同的情况下自动重命名;

(3) 输出 HDFS 文件内容: 实现了将 HDFS 中指定文件的内容输出到终端;

(4) 显示 HDFS 文件信息: 编程实现了显示 HDFS 中指定文件的读写权限、大小、创建时间、路径等信息;

(5) 显示 HDFS 目录信息: 实现了给定 HDFS 中某一个目录, 输出该目录下所有文件的读写权限、大小、创建时间、路径等信息, 包括递归输出子目录下的文件信息;

(6) 创建和删除 HDFS 文件: 编程实现了提供一个 HDFS 内的文件路径, 对该文件进行创建和删除操作。如果文件所在目录不存在, 程序会自动创建相应目录;

(7) 创建和删除 HDFS 目录: 实现了提供一个 HDFS 目录的路径, 对该目录进行创建和删除操作。创建目录时, 如果目录所在目录不存在, 程序会自动创建相应目录。删除目录时, 用户可以指定当该目录不为空时是否还删除该目录;

(8) 追加 HDFS 文件内容: 编程实现了向 HDFS 中指定的文件追加内容, 允许用户选择是追加到文件的开头还是结尾;

(9) 删除 HDFS 文件和目录: 实现了删除 HDFS 中指定的文件或目录。对于目录, 用户可以指定是否删除包含文件的目录;

(10) 移动 HDFS 文件: 编程实现了在 HDFS 中将文件从源路径移动到目标路径。

2. 实现自定义 HDFS 文件读取类

实现了一个自定义 HDFS 文件读取类 "MyFSDataInputStream", 该类继承自 "org.apache.hadoop.fs.FSDataInputStream", 并实现了按行读取 HDFS 中指定文件的方法 "readLine()". 这允许用户以更高级的方式按行读取 HDFS 文件的内容。

3. 使用 Java 和 URL 读取 HDFS 文件

编写 Java 程序, 使用 "java.net.URL" 和 "org.apache.hadoop.fs.FsURLConnectionHandlerFactory", 实现了输出 HDFS 中指定文件的文本到终端的功能。这为从 HDFS 中读取文件并在终端上显示文件内容提供了一种方法。

总而言之, 所有实验任务均完成并达到预期。

本次实验使我们能够深入了解 HDFS 的操作和 Hadoop 的相关工具, 包括 Shell 命令和自定义 Java 编程。这些技能对于大数据处理和分布式文件系统操作非常重要, 有助于我们在大数据领域获得更多经验。

六、 问题和解决

问题 1:

通过 Path 类标识 HDFS 中的文件和目录位置时，可能出现路径错误或无法找到文件的问题。

解决方案:

确保使用正确的 HDFS 路径格式，如 `hdfs://<namenode>:<port>/path/to/file`，并检查文件或目录是否存在。在调用 `FileSystem` 类的 `copyFromLocalFile` 方法之前，可以使用 `Path` 构造器创建正确的路径对象。

问题 2:

通过 `FileSystem` 类的 `copyFromLocalFile` 方法将文件从本地文件系统复制到 Hadoop 文件系统时，可能会出现复制失败或权限问题。

解决方案:

确保指定的本地文件存在，HDFS 路径有效，且有足够的权限执行复制操作。检查 Hadoop 集群的连接是否正常，确保网络通畅。还要注意端口和配置是否正确。

问题 3:

使用 `FileSystem` 的 `copyToLocalFile` 方法从 HDFS 中的 `remotePath` 下载文件到新的本地路径 `localPath` 时，可能出现复制失败或文件不存在的问题。

解决方案:

确保 HDFS 中的 `remotePath` 存在并且包含正确的文件名，`localPath` 指定了有效的本地目录。还要注意权限问题，确保您有权限读取 HDFS 中的文件。

问题 4:

使用 `FileSystem` 对象的 `open` 方法打开文件后，可能遇到无法读取文件内容的问题。

解决方案:

确保文件存在并且指定的路径正确。如果文件不存在，将无法打开它。如果路径正确，但读取失败，可以检查 HDFS 权限是否足够。另外，确保 Hadoop 集群运行正常。

问题 5:

在创建 `InputStreamReader` 和 `BufferedReader` 时可能会出现编码问题或流处理错误。

解决方案:

确保使用正确的字符编码，通常是 UTF-8。您还应确保正确处理异常，如在创建 `InputStreamReader` 时捕获 `IOException`。使用 `BufferedReader` 允许逐行读取文本，这是一种更高效的方式。

问题 6:

Hadoop 环境配置不正确，导致 HDFS 操作失败。

解决方案:

确保 Hadoop 的配置文件（如 `core-site.xml` 和 `hdfs-site.xml`）正确设置，包括 HDFS 的 URI 和相关属性。检查 Java 环境变量和 Hadoop 安装路径是否正确。

问题 7:

在使用 Java URL 处理 HDFS 文件时出现问题。

解决方案:

确保使用正确的 URL 格式来引用 HDFS 文件。检查 URL 处理程序是否正确设置。查看 Java 文档和 Hadoop 文档以获取更多信息，如果遇到问题仍无法解决，可以寻求 Hadoop 社区或论坛的帮助。